

Appl. No. 10/782,322  
Atty. Docket No. 9164M  
Amdt. dated 6/29/2005  
Reply to Office Action of 02/08/2005  
Customer No. 27752

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-46 (Cancelled)

Claim 47. (*Currently Amended*) A method of cleaning a surface comprising:  
providing a cleaning sheet having a first side and a second side, wherein said first side comprises a first additive, wherein said first additive is present on said first side at a level of between about 0.1 g/m<sup>2</sup> and about 2.3 g/m<sup>2</sup>, wherein said first additive comprises a micro-crystalline wax, wherein said first additive has a penetration value at 25°C of between about 20 dmm and about 100 dmm and wherein said first side has a Relative Tack Rt which is between about 55% and about 94%; and  
wiping said surface with said cleaning sheet.

Claim 48. (Cancelled)

Claim 49. (Cancelled)

Claim 50. (Original) The method of claim 47 wherein at least one of said first or second sides comprise instructions printed on said first or second sides.

Claim 51. (*Currently Amended*) The method of claim 47 wherein said first additive additive further comprises a colored dye.

Claim 52. (*Previously Presented*) The method of claim 47 wherein said cleaning sheet comprises at least one layer of nonwoven material.

Claim 53. (*Previously Presented*) The method of claim 52 wherein said cleaning sheet has a basis weight of at least about 40 g/m<sup>2</sup>

Appl. No. 10/782,322  
Atty. Docket No. 9164M  
Amdt. dated 6/29/2005  
Reply to Office Action of 02/08/2005  
Customer No. 27752

**Claim 54. (Previously Presented)** The method of claim 53 wherein said cleaning sheet has a basis weight of between about 50 g/m<sup>2</sup> and 90 g/m<sup>2</sup>.

**Claim 55. (Cancelled)**

**Claim 56. (New)** The method of claim 46 wherein said first additive has a penetration value at 25°C of between about 25 dmm and about 90 dmm.

**Claim 57. (New)** The method of claim 56 wherein said first additive has a penetration value at 25°C of between about 25 dmm and about 80 dmm.

**Claim 58. (New)** The method of claim 46 wherein said first side has a Relative Tack Rt which is between about 60% and about 92%.

**Claim 59. (New)** The method of claim 58 wherein said first side has a Relative Tack Rt which is between about 65% and about 90%.